# SOUND LEVEL **DATALOGGER**


## Model : C

### **FEATURES**

- RS232 Interface
- 32,000 Records Datalogger
- **Bargraph Indication**
- MAX / MIN Function
- Auto Ranging (30~130dB)
- Resolution 0.1 dB
- Clock Display
- Level Range Display

If one needs long time on site sound monitoring, C 322 will be the choice. With its built in 32000 records deep memory, it can gather all the data you need just by this tester.

Meter Display gives the decibel level, Bargraph display, with either fast or slow time weighting. After the data is collected, the user can download the data to the computer at his convenient place.



SPECIFICATION	
Level Range	Lo = $30 \sim 80$ dB; Med = $50 \sim 100$ dB; Hi = $80 \sim 130$ dB
Accuracy	± 1.5dB (ref 94dB@ 1KHz)
Frequency Weighting	A / C
Time Weighting	Fast, Slow
Dynamic Range	50dB
Frequency Range	31.5Hz to 8KHz
Microphone	Electret condenser microphone
Auxiliary Outputs	AC / DC Output
Battery	9V battery
Dimensions	275 × 64 × 30 mm

#### Standard Accessories

Battery, Operation Manual, Carrying Case, Calibration Screwdriver, Windscreen, 3.5 \phi plug, Software, RS 232 cable.



An ISO 9001: 2015 Certified Company



Website: www.ankom.co.in E-mail: info@ankom.co.in, sales@ankom.co.in