


POCKET CONDUCTIVITY / TDS / TEMPERATURE METER



Boiler Water



Cooling Water



Water Treatment




Process Water



Drinking Water



Swimming Pool



Aquaculture



Waste Water

Features

- Big LCD Dual Display
- IP65 Water Proof
- Stability Indication
- Quick Response
- Auto Temperature Compensation
- One Touch Auto-Calibration
- Auto Ranging or Manual Ranging
- Calibration Values are Adjustable
- 20 Mins Auto Power off
- Simple Sleep Mode Disable
- Data Hold Function
- Low Battery Indicator
- Temperature Unit Selectable

Specifications

Measuring Range	5~1999 μ S/ppm or 0~19.99mS/ppt
Measuring Accuracy	+/-1%FS +/- 1 digit
Resolution	1 μ S/1ppm or 0.01mS/0.01ppt
Temp. Range	0~50.0 $^{\circ}$ C
Temp. Accuracy	+/-0.5 $^{\circ}$ C
Temp. Resolution	0.1 $^{\circ}$ C
ATC	Yes
TDS Factor	0.4~1.00
Temp. Coefficient	0~4.0%/ $^{\circ}$ C
LCD Size	30(H)x18(W)mm
Operating Temp.	0~50 $^{\circ}$ C
Operating RH%	Humidity < 80%
Storage Temp.	0~60 $^{\circ}$ C
Storage RH%	Humidity < 90%
Dimension	165(L)x35(W)x32(H)mm
Weight	115g
Battery	LR44 x 4pcs
Standard Package	Meter/Battery/Manual/Paper box

Equinox[™]



EQ - 8361



ANKOM INTERNATIONAL

An ISO 9001: 2015 Certified Company
Your Instrument Super Store

71, Ramachandra Agrahara, Azad Nagar, Chamarajpet, Bangalore - 560 018. INDIA • Phone: 080-2674 1381 Tele/Fax: 080-2674 1382
Website : www.ankom.co.in E-mail : info@ankom.co.in, sales@ankom.co.in

